

## Customer Setup

**Step 1:** For this Setup you need two devices (one for Teller/Cashier display and other for Customer display).

**Step 2:** And make sure Both the IPADs are connected to same **WIFI** network.

**Step 3:** On **Customer display** IPAD, go to IOS “Settings “→WIFI → Tap on Network to which it is connected. And note down the “IP address”

- Open DolphinPOS APP, login with the user credentials and
- go to” More” → “Customer display config”
- Configure:
  - IP Address: copy from above step3
  - Port No:13000 (always Fixed)
  - Turn ON flags “is service server” and
  - “Enable customer display”.

**Step 4:** In the **Teller /cashier** IPAD

- Open DolphinPOS APP, login with the user credentials and
- Go to” More” → “Setup” → “UDP Config.”
- Configure:
  - IP Address: copy from above step3 (of customer display)
  - Port No:13000 (always Fixed)
  - Turn ON flags “is service client” and
  - “Enable customer display”

**Step 5:** Now **Close** the DolphinPOS App on both the IPADs. First turn ON Teller/cashier IPAD and then turn ON customer display IPAD.

On Teller/cashier IPAD: Go to “Register” Screen

On customer display IPAD: Go to “More” → “Customer display config” → click the button “Display screen”

**Step 6:** Once you start adding items in Teller/cashier IPAD, and then should see same items getting displayed on customer display IPAD.

**\*\* Now you are good to go!! \*\***